

BlueFlex®

FASTENERS SYSTEMS



Exclusive Piloted Bolts:
Tapered tips that cradle nuts securely in place.
Reduce installation time.
Easy to use.

Selection Guide

Fastener Size	Belt Thickness Range		For Belts with Mechanical Fastener Ratings Up To:		Minimum Pulley Diameter	
	in.	mm	Pl.W.	kN/m	in.	mm
1	3/16 - 7/16	5 - 11	150	30	12	300
140, 140VP	3/16 - 7/16	5 - 11	225	40	14	360
190, 190VP	5/16 - 9/16	8 - 14	375	65	18	460
1-1/2	7/16 - 11/16	11 - 17	300	50	18	460
2, 2VP	9/16 - 13/16	14 - 21	440	75	30	760
2*	15/16 - 1-1/4	8 - 32	700	123	20	510
2-1/4	9/16 - 1-3/16	14 - 30	620	105	36	920
2-1/2	3/4 - 1	19 - 25	450	75	42	1070
3	15/16 & over	24 & over	560	100	48	1220

* When used with No. 3 Lead Wedlok® pattern, belts over 7/8" (22 mm) require extra long No. 2-1/4 bolts

Redbelt PREMIUM®
Se mueve conmigo®



(871) 192-7704



www.redbelt.com.mx



Bvd. Revolución 1539 Ote. Torreón, Coah.